

CES-RJ19-W46A

嵌入式无风扇边缘计算系列

**Intel® Bay Trail J1900 处理器, 四核, TDP 10W, 无风扇
四个网口, 六个串口, 四个USB, 9-36V宽压输入**


采用Intel® Bay Trail J1900 处理器, 拥有丰富I/O接口, 高度灵活性以及支持不同扩展接口的工业电脑, 而且具有适应宽温、坚固机构的特性, 可广泛应用于工业自动化、自助设备、仓储管理、智能制造等领域。



板载Intel® Celeron® J1900高性能低功耗四核处理器, 主频最大可以达到2.0GHz
支持单通道DDR3L 1333 SO-DIMM内存插槽, 内存容量最大可达8GB
支持四个千兆网口
支持VGA/HDMI多扩展显示
内置1 x 2.5寸HDD/SSD可扩充支架
内置Mini-PCIe及M.2支持多种模块扩展
9~36V宽压设计, 可锁附DC-IN接口



■ 尺寸 Dimension (Unit:mm)



■ 规格 Specification

系统 System		外部接口 External I/O	
处理器 Processor	Intel® Bay Trail Celeron® J1900 processor (2.0 GHz)	网口 Ethernet	4 x RJ45 Intel® i211AT GbE (10/100/1000 Mbps)
内存 Memory	1 x DDR3L 1333 MHz SDRAM Slot, up to 8GB	显示 Video	1 x VGA: max resolution up to 2560 x 1600 1 x HDMI: max resolution up to 1920 x 1200
图形 Graphics	Intel® HD Graphics for Intel Atom® Processor Z3700 Series, dual display	音频 Audio	1 x Audio(Line-out&Mic-in 2 in 1), Realtek® ALC269 HD Audio codec
存储 Storage	1 x 2.5" SATA 2.0 HDD/SSD bay 1 x mSATA/M.2 2242 SSD slot	串口 COM	6 x COM (2 x RS232/422/485 auto-flow, 4 x RS232/485 optional by jumper)
操作系统 OS	Windows 7/8/10, Linux	USB	3 x USB 2.0, 1 x USB 3.0
看门狗定时器 Watchdog Timer	Programmable 255 levels timer interval, from 1~255 sec/min	GPIO	1 x 8bit programmable GPIO
机构 Mechanical		按钮 Button	1 x Power button
外观 Housing	铝合金 Aluminum Alloy	指示灯 LED	1 x Power LED (Green for Power-on, Blink for Sleep mode, Off for Power-off)
安装方式 Mounting	桌面式 (Desk-Mount), 壁挂式 (Wall-Mount) VESA-mount (75 x 75mm, 100 x 100mm), 导轨式 (DIN-Rail)	远程开关 Remote ON-OFF	1 x Remote ON-OFF
尺寸 Dimension	244 x 153 x 57.5 mm	内部接口 Internal I/O	
重量 Weight	1.9kg	扩展接口 Expansion	1 x Full-size Mini-PCIe Slot(co-lay with mSATA) 1 x M.2 2242 slot (only support SSD) 1 x M.2 2230 slot for Wifi module
环境 Environmental		SIM 卡	1 x SIM Card Slot
操作温度 OperatingTemp.	-10°C ~ 60°C (SSD), 0°C ~ 40°C (HDD)	电源 Power	
存储温度 Storage Temp.	-40°C ~ 85°C	电源输入 Power Input	9~36V DC, 2-pin phoenix connector
湿度 Relative Humidity	5% ~ 95%, 非凝结状态 Non-condensing	认证 Certification	
振动 Vibration	SSD: 5~500Hz, 2Grms operation HDD: 5~500Hz, 1Grms operation	安规认证 Safety Certification	CCC, CE, FCC
机械冲击 Shock	Operation: 10G@11ms Non-operation: 30G@11ms		

■ 配置 Configuration

型号 Model Name	网口 Ethernet	USB
CES-RJ19-W26A	2	6
CES-RJ19-W46A	4	4

■ 订购清单 Order List

标准 Standard	型号 Model Name	描述 Description	选配 Optional	型号 Model Name	描述 Description
	CEA-SA15-CAB2	1xSATA, 7+4P,150mm, w/o lock, 180° / 90°		CEA-150L-IS00	150cm AC power cord
CEA-GP00-CON0	1x8bit GPIO conn (3.50), female	CEA-060W-FSP0	FSP 60W adapter, 12V@5A, 2PIN terminal		
CEA-M242-FAN0	1xM.2 2242 SSD thermal pad	CEA-060W-HK00	Huntkey 60W adapter, 12V@5A, 2PIN terminal		
CEA-PWDC-CAB0	1x2P DC in Phoenix conn(5.00), female	CEA-CM15-CAB0	1xCOM, 2x5P, 150mm, black		
CEA-RESW-CAB0	1x2P Remote Phoenix conn (3.50), female	CEA-MKIT-R000	VESA-Mount and DIN-Rail kit		



产品配置请以合同或实物为准, 如有修改恕不另行通知;
版权为桦汉科技所有, 未经桦汉科技书面许可, 样本中的任何内容不得被复制或抄袭用于任何目的。

©Printed in China
Number: MKT1005A0A-2-12(20.02.17)